

Motorenstrasse 102 CH-8620 Wetzikon

Telefon +41 (0)58 272 01 01 Telefax +41 (0)58 272 01 03 info@kisling.com www.kisling.com

## **TECHNICAL DATASHEET**

# ergo® REMOVER 9150

(for anarobic adhesives as well as for cyanoacrylics, superglue)

#### DESCRIPTION

The erg® adhesive REMOVER 9150 is based on solvents with low vapor pressure, which are evaporating very slowly. Due to this behaviour, it remains long time on the wetted surface and may penetrate even cured films.

The product is also suitable to solve liquid residue of anaerobics and superglue

#### **USAGE**

The REMOVER can be applied either on the cured film, or the bonded parts may be dipped and stored directly in the ergo® 9150.

The needed time depends on film thickness, shape, gap and environmental temperature and must be tested in advance.

wrgo® 9150 soaks the polymer film and makes it possible to remove it mechanically Elevated temperature (max. 45°C) and/or Ultrasonic treatment will accelerate this procedure. In case of the use of bigger quantity, take steps against electric charge.

#### **ATTENTION!**

Please check carefully in advance, whether the bonded material resists against the solvents.

### **Physical properties**

Chemical base organic solvents

Colour colouless / slightly yellow (pale)

Viskosity < 20 mPas

Density 0,85 - 0,94 g/cm<sup>3</sup> at 20°C

Flash point > 90 °C acc. to DIN 55213

Shelf life 18 month at approx. 20°C

#### WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that KISLING products are safe, effective, and fully satisfactory for the intended end use. KISLING sole warranty is that the product will meet the KISLING sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. KISLING specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Unless KISLING provides you with a specific, duly signed endorsement of fitness for use, KISLING disclaims liability for any incidental or consequential damages. Suggestions of uses should not be taken as inducements to infringe any particular patent.